



FEATURES

Case PILOT Z1 - 1L, MB H610T3, 2xType-C, 4xUSB3, 2xUSB2, HDMI, WiFi6 & BT, RJ45, Vesa, 120W PSU

SPECIFICATIONS

Form Factor
Case volume
Chassis
PSU Form Factor
M/B Form Factor
Front Panel
Top Panel
Left Side Panel
Right Side Panel
Internal Drive Bay 2.5" (SSD)
I/O Buttons
USB3.1 Port(s)
Type-C 2.0
HD Audio Support
Security

Thin Mini ITX
1 liters
SGCC 0.6mm
External DC adapter 120W
Thin Mini ITX Asus(R) H610T3
Plastic: ABS
Metal cover
Metal cover
Metal cover
*1
*1
*2
*1
*1

Cable cover, Kensington lock,
Security screw
AX201NGW
Intel® Wi-Fi serie 6
5.2
Yes, internal
Yes, 100x100
(L)179*(W)37*(H)183mm
(L)186.5*(W)37*(H)183mm

(L)253*(W)84*(H)225mm K3K
1,4kgs
1,7kgs
19mm

WiFi Module
WiFi Version
Bluetooth Version
WiFi Antenna
VESA
Dimension Chassis
Dimension Full Case (inc Fascia)
Carton
Net Weight (Kg)
Gross Weight (Kg)
CPU Cooler Height

MOTHERBOARD
Motherboard
Chipset

Asus® PRIME H610T3-CSM D4
Intel® H610 Chipset

CPU

Intel® Socket LGA1700 for 12th Gen Intel® Core™, Pentium® Gold and Celeron® Processors*

Memory

*CPU only support up to 65W
2 x SO-DIMM, Max. 64GB, DDR4 3200/3000/2933/2800/2666/2400/2133 Non-ECC, Un-buffered Memory*

Back I/O Ports

1x HDMI® (Supports 4K@60Hz as specified in HDMI 2.1)
2 x USB 3.2 Gen 2 ports (1 x Type-A + 1 x Type-C)
2 x USB 2.0 ports (2 x Type-A)
1 x Realtek 1Gb Ethernet port
2 x Audio jacks

Storage

1 x DC Power Connector (Support 19V)
Total supports 1 x M.2 slot and 2 x SATA 6Gb/s port
- 1 x M.2 slot (Key M), type 2260/2280 (supports PCIe 4.0 x4 & SATA modes) *
- 2 x SATA 6.0 Gb/s ports

Lan

1 x Realtek RTL8111H 1Gb Ethernet (Asus® LANGuard)

Thermal Kit

Approved thermal module Kit for Core i3/5/7 CPU up to 65W TDP

PACKING INFORMATION

Code: ITOCPZ1
EAN: 8056157882985

SOCIAL MEDIA COMMUNICATION

