



FEATURES

Itek AIO Barebone - 27" FHD, H610, WiFi, BT, Pop-Up Cam, Spkr, Type-C, USB3, CR, HAS Stand

SPECIFICATIONS

<p>Display</p> <p>Motherboard</p> <p>Chipset</p> <p>CPU</p>	<p>27 inch, FHD (1920 x 1080) 16:9, IPS level, Wide-Angle View, Anti-glare, LED backlight, 250 nits, 1:1000 contrast ratio, 3-Border Bezel-free, Zero Bright dot</p> <p>ASUS® H610T Thin Mini ITX</p> <p>Intel® H610 Chipset</p> <p>Intel® Socket LGA1700 for Intel® Core™ 14th & 13th Gen Processors, Intel® Core™ 12th Gen, Pentium® Gold and Celeron® Processors*</p> <p>Supports Intel® Turbo Boost Technology 2.0 and Intel® Turbo Boost Max Technology 3.0**</p> <p>*CPU only support up to 65W</p> <p>*Refer to www.asus.com for CPU support list.</p> <p>**Intel® Turbo Boost Max Technology 3.0 support depends on the CPU types.</p>
<p>Memory</p>	<p>2 x SO-DIMM, Max. 64GB, DDR5 5600 Non-ECC, Un-buffered Memory*</p> <p>Dual channel memory architecture</p> <p>*Actual Memory data rate support depends on the CPU types and DRAM modules, for more information refer to www.asus.com for the Memory QVL [Qualified Vendors Lists].</p>
<p>Graphics</p>	<p>1 x DisplayPort**</p> <p>1 x HDMI™ port***</p> <p>1 x LVDS connector</p> <p>*Graphics specifications may vary between CPU types.</p> <p>** Supports max. 4K@60Hz as specified in DisplayPort 1.4.</p> <p>*** Supports 4K@60Hz as specified in HDMI 2.1.</p>
<p>Storage</p>	<p>Total supports 1 x M.2 slot and 2 x SATA 6Gb/s ports</p> <p>Intel® Core™ Processors (14th & 13th & 12th Gen)</p> <p>- 1 x M.2 slot (Key M), type 2260/2280 (supports PCIe 4.0 x4 & SATA* modes)</p> <p>Intel® H610 Chipset</p> <p>- 2 x SATA 6.0 Gb/s ports</p> <p>*The SATA lane source is Intel® H610 Chipset.</p>



Ethernet

1 x Realtek 1Gb Ethernet
ASUS LANGuard

Wireless
Front I/O

Wi-Fi AC + Bluetooth 5
1 X USB 3.2 Type C
*Support Quick Charging

Back I/O

1 x USB 3.2 Type A
1 x 3.5mm Audio Combo Jack
1 x Card Reader
2 x USB 3.2 Gen 2 ports
2 x USB 2.0 ports
1 x DisplayPort
1 x HDMI port
1 x Realtek 1Gb Ethernet port
2 x Audio jacks
1 x DC Power Connector (Support 19V)

Speakers
Security

2 x 3W Speakers
Kensington Lock
Cable Cover

Power
Camera
Height Adjustable
Stand

120W Adaptor
Pop-Up Camera Housing - 5Mp 2592x1944 Camera With Dual Microphone

Tool-Less Quick Release / Install Design
Elevation: 130 mm
Tilt: -15° -25°
Swivel: -30° -30°
Rotation: -90° -90°

Cover
Thermal Kit
VESA
Profile
Dimension

Black Matt with Circle White Light
Approved thermal module Kit for Core I 3/5/7 CPU up to 65WTDP
Supported with ITEK custom bracket (optional)
48mm thick

(Without Stand) 616.13 x 379.29 (H) x 55 (D) mm
(With Adjustable Stand) 616.13 x 539.57 ~ 409.57 x 230mm

Chassis Material

ABS Carbon Fibre rear cover, Plastic stand

PACKING INFORMATION

SOCIAL MEDIA COMMUNICATION

Codice: ITPCAB2761BHW
EAN: 8056157884002

